

# Reducer Bushing Feed-Through



Feed-Through Reducer Bushings are used for reducing to a smaller wireway size. The center hole bushing centers the two wireway sizes relative to each other while the edge hole bushing keeps the top surfaces even. Connects to other wireway sections and fittings and protects wires and cables against dust in a broad range of industrial applications.

## INDUSTRY STANDARDS

---

Certified by Canadian Standards Association.

## FEATURES

---

Feed-Through Reducer Bushings are used for reducing to a smaller wireway size

The center hole bushing centers the two wireway sizes relative to each other while the edge hole bushing keeps the top surfaces even

Connects to other wireway sections and fittings and protects wires and cables against dust in a broad range of industrial applications

## SPECIFICATIONS

---

**Color Code:** ANSI 61  
**Color:** Gray  
**Material:** Mild Steel  
**Finish:** Powder Coated

Table 1/1

| Catalog Number | Article Number | Type    | Height | Width | Thickness |
|----------------|----------------|---------|--------|-------|-----------|
| F88WRE66       | 14770          | Reducer | 6in    | 2.5in | 14ga      |
| F88WRE44       | 14790          | Reducer | 4in    | 2.5in | 14ga      |
| F88WR66        | 14760          | Reducer | 6in    | 2.5in | 14ga      |
| F88WR44        | 14780          | Reducer | 4in    | 2.5in | 14ga      |
| F66WRE44       | 14580          | Reducer | 4in    | 6in   | 14ga      |
| F66WR44        | 14570          | Reducer | 4in    | 6in   | 14ga      |
| F44WRE22       | 14370          | Reducer | 2in    | 4in   | 14ga      |
| F44WR22        | 14360          | Reducer | 2in    | 4in   | 14ga      |

## ADDITIONAL PRODUCT DETAILS

---

All dimensions are to outside surfaces. Allow .12 in. (3 mm) additional for gasket at joints.

## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**